

# GLYCOL POWER PACKS



**1/3 and 1/2 HP Power Pack**



**1 HP Glycol Power Pack**

Air-cooled remote glycol chiller. Maintains constant beer temperature. Easily accessible sealed food-grade glycol bath incased in a corrosion resistant reservoir. The all-metal cabinet has a hinged cover and removable panels that provide easy access for service and cleaning. Available in 1/2, 1/3, and 1 HP units. These units have easy to read glycol bath and glycol return temperature gauges and illuminated power switches conveniently located at the front of the unit. UL, CUL, and MEA listed. Warranty: 90-day labor, 1-year parts, and 5-year compressor.

## SPECIFICATIONS

Glycol Power Pack Part Number	BR35	BR55	BR1000	BR1000X
Maximum Distance	170	275	500	500
Refrigerant Type	R-22	R-22	R-22	R-22
Compressor HP, 60 Hz/1 Phase	1/3	1/2	1	1
Start Amps	29	36	60	34.2
Run Amps	7.05	7.98	13.2	7.0
Circulating Motors HP-115V/60Hz	1/3	1/3	1/3	1/3
	115V	115V	115V	208-230V
Run Amps	6.1	6.1	5.6	5.6
Required Fuse/Minimum Circuit (Amps)	20	20	30	25
Circulating Pump, GPH (adjustable)	100	100	100	100
Reservoir Capacity-Gallons	7	7	13	13
Inlet and Outlet Thermometers	Yes	Yes	Yes	Yes
Illuminated Power Switches	Yes	Yes	Yes	Yes
Dimensions				
	Width	20"	20"	24"
	Depth	33"	33"	33"
	Height	20"	20"	31"
Additional Pump and Motor Assemble*	2	2	3	3

\* 1 HP Units Require A Neutral Wire

\* All Double Pump 1/3 and 1/2 HP Models Require 30 Amps



**AC BEVERAGE, INC.**  
DRAUGHT BEER SPECIALISTS

1993-7 Moreland Pkwy ♦ Annapolis, MD 2140

800-925-3818

Tel: (410) 268-0714 ♦ Fax: (410) 268-8300